



STOP...READ THIS FIRST!!!
#33143 SPRING HANGERS
88-98 CHEVY/GMC TRUCK

***MUST USE WITH DROP SHACKLES #33037.**



Kit Includes:

- (2) Hanger Brackets
- (1) Emergency Brake Cable Bracket
- All Hardware

1. Place a block in front of wheels and jack up rear of vehicle placing floor jacks under the frame in front of the rear suspension.
2. Using a jack under the rear end, raise the vehicle up enough to take the weight off the front spring hangers.
3. Drop the gas tank down, disassemble any brackets, straps, clips, and disconnect the gas filler neck so that the gas tank can slide over. Allow yourself enough room to remove your hanger and install our hanger.
4. Drill out the rivets that hold the hangers to the frame.
5. Lower the axle to allow the hanger and spring to drop below the frame.
6. Unbolt and remove the leaf spring.
7. Make sure the new hanger area has a smooth surface to install to.
8. Bolt the leaf spring to the new hanger and then the hanger to the frame. (Bolt the leaf spring eye bolt through the hanger and leaf spring so the nut is facing outward)
9. Be sure to not over tighten the bolt through the spring eye because the leaf has to be able to rotate within the hanger.
10. Bolt in your new McGaughy's hangers on each side.
11. Cut your bump stops in the rear of the truck so that one inch is left on your bump stop. Cutting the bump stop in half is fine!!
12. Install gas tank using all original straps, clips, and brackets.
13. Install spring shackles now following shackle instructions.
14. Adjust the position of the center drive-line carrier bearing and pinion angle if needed.
15. Lower truck down and remove jack stands.

